

## Reach-in Refrigerators

SOLID DOORS REFRIGERATORS  
GLASS DOORS REFRIGERATORS



The Asber ARR H / ARR series reach-in refrigerators are engineered to be the cornerstone of any commercial kitchen, offering unparalleled durability, hygiene, and efficiency. These units feature a robust stainless-steel exterior on the front and sides, complemented by a galvanized back, making them ideal for the demanding restaurant environment. The interior is crafted entirely from stainless steel, providing the most rugged construction while ensuring easy cleaning. The coved corner floors meet NSF standards, elevating the unit's sanitation capabilities and setting a new benchmark in food safety.

Insulation plays a crucial role in the thermal efficiency of these refrigerators. Asber exclusively uses the world-renowned "Ecomate™" insulation, known for its superior Global Warming Potential (GWP) and Ozone Depletion Potential (ODP) ratings. At 2-3/8" thick (ARR H series) and 2" (ARR series), this insulation delivers the highest R-value efficiency, ensuring optimal temperature control in various kitchen environments.

Designed with the operator in mind, these reach-ins feature ergonomically designed full-length door handles suitable for various user heights. The in-step interior design creates a superior seal, effectively preventing sweating. The magnetic one-piece door gasket can be removed without tools, simplifying cleaning and replacement procedures.

Asber's commitment to eco-friendly innovation is evident in their use of R290 Hydrocarbon refrigerant. This advanced refrigerant meets the DOE's Energy Conservation standards while minimizing environmental impact with its low global warming contribution (ODP-0, GWP-3).

For enhanced visibility and energy efficiency, the "G" models feature double-pane, hinged glass doors with argon gas insulation. This specialized design prevents heat transfer, minimizes condensation, and provides a frost-free viewing environment, making it easier for staff to locate items without unnecessary door openings.

### ADDITIONAL FEATURES TO INCLUDE

- Doors lock with universal key.
- Hermetic compressors with epoxy coated evaporator.
- Field reversible doors on solid single door units.
- Automatic evaporator: paper fins not utilized in the evaporation process.
- Electronic controller with digital display.
- Temperature: 32 °F to 38 °F based on an external environment of 100°F and 65% RH.
- Standard with 2-1/2" castors (17 ft<sup>3</sup> models) or 5" castors (37 ft<sup>3</sup> models), front with brakes.
- LED lighting in both solid and glass door units for clear visibility.
- NSF-7 certified, meeting stringent food safety standards.



ARR-23-H



ARR-37-2G-H



ARR-72-H

MODEL	DOORS	SHELVES	CAPACITY ft <sup>3</sup>	VOLTS - FREQUENCY	POWER HP	AMP	EXTERIOR DIMENSIONS (in)			SHIPPING	
							Width	Depth	Height	Lbs	ft <sup>3</sup>
<b>SOLID DOORS REFRIGERATORS</b>											
ARR-17	1	3	17.0	115V. - 60 Hz.	1/4	2.5	27-1/2	26-3/4	77-1/8	271	45.9
ARR-23-H	1	3	23.0	115V. - 60 Hz.	1/4	2.5	27-1/2	31-1/8	84-3/4	293	56.5
ARR-37-H	2	6	37.0	115V. - 60 Hz.	1/3	3.2	43-1/2	32-1/4	84	437	74.2
ARR-49-H	2	6	49.0	115V. - 60 Hz.	1/3	3.2	55-3/8	31-1/8	84-3/4	459	105.9
ARR-72-H	3	9	72.0	115V. - 60 Hz.	2 x 1/3	7.5	82-5/8	32-1/4	84-3/4	664	134.2
<b>GLASS DOORS REFRIGERATORS</b>											
ARR-23-1G-H	1	3	23.0	115V. - 60 Hz.	1/4	2.5	27-1/2	31-1/8	84-3/4	293	56.5
ARR-37-2G-H	2	6	37.0	115V. - 60 Hz.	1/3	3.2	43-1/2	32-1/4	84	437	74.2
ARR-49-2G-H	2	6	49.0	115V. - 60 Hz.	1/3	3.2	55-3/8	31-1/8	84-3/4	459	105.9
ARR-72-3G-H	3	9	72.0	115V. - 60 Hz.	2 x 1/3	7.5	82-5/8	32-1/4	84-3/4	664	134.2

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. | SPECIFICATIONS VALID ONLY FOR CONTINENTAL USA & CANADA.