

"WE MAKE THE KITCHEN BETTER!"

Toll Free: 855-855-0399 Email: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, Massachusetts, New Jersey, Ohio, Texas, Washington

MODELS:

MBF8010GR / MBF8010GRL

Top Mount 1/2 Door Reach-In Refrigerators

Standard Features

- Top mount compressor with environmentally friendly R290 refrigerant
- Stainless steel exterior & interior
- Dixell digital controller
- Maintains temperatures between 33°F 40°F
- LED interior light(s)
- Recessed door handle(s)
- Door lock(s) standard
- Magnetic door gasket(s) standard for positive door seal
- Pre-installed casters
- Three(3) pre-installed shelves standard
- Down duct refrigeration to ensure even distribution of air

Optional Accessories

 Extra shelves – includes 4 shelf clips per shelf, shelf part #: W0402389



MBF8010GR



MBF8010GRL *L indicates left hand model

For the best results of food preservation we recommend setting your refrigerator between 33 $^\circ F$ to 38 $^\circ F$

- 1. Don't forget to leave the unit some room to breathe!
- 2. Please clean the condenser frequently to give the unit more fresh air.



2 YEAR PARTS AND LABOR WARRANTY (US ONLY) 5 YEAR COMPRESSOR PART WARRANTY (US ONLY)



For confirmation and updates on the latest energy star models, please visit energystar.gov



"WE MAKE THE KITCHEN BETTER!"

Toll Free: 855-855-0399 Email: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, Massachusetts, New Jersey, Ohio, Texas, Washington

SPECIFICATIONS

Models	Door	Capacity (Cu.Ft.)	Shelves	Casters (inch)	Amps (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lbs)	Gross Weight (lbs)
MBF8010GR MBF8010GRL	2	21.4	3	4	2.1	115/60/1	1/7	R290	28 ^{7/10} ×31 ^{7/10} ×81 ^{3/10}	254	271

PLAN VIEW

MBF8010GR MBF8010GRL 287/10 287/10 317/10 813/10 813/10 *25 *60^{5/8} ø T 6 Ċ ð 8 *Interior Dimensions SELF-CLOSING AND STAY OPEN DOOR FEATURE 585/8 24 1050 Epoxy shelves Casters Door lock Down duct Temperature control



