

| Project:  | AIA# |
|-----------|------|
| ltem:     |      |
| Location: | SIS# |
| Approved: |      |

## RI REACH-IN REFRIGERATOR

RI18HC Half-Solid Door Bottom Mount Refrigerator Hydrocarbon Series

MODEL: RI18HC-HS



7 Year Parts/Labor Warranty7 Year Compressor Warranty

### **CABINET CONSTRUCTION**

- · Stainless steel exterior and interior
- Full electronic control
- Interior LED light
- Five (5) shelves standard
- · One piece grille
- Self-closing doors with 120° stay-open feature, on spring loaded hinges
- Snap-in magnetic door gaskets
- 3" Heavy duty casters with two brakes standard

### **OPTIONS & ACCESSORIES**

- · Epoxy shelves & clips
- 6" Casters or 6" legs optional
- · Wire shelf dividers
- · Right or left hinged door
- Remote option\* (see note on back page)

# **REFRIGERATION SYSTEM**

- Refrigeration system uses R290 refrigerant to comply with all environmental concerns
- Automatic, non-electric defrost
- · Epoxy coated evaporator coil
- Maintains temperature between 36° and 38°F








| MODEL                        | RI18HC-HS             |  |
|------------------------------|-----------------------|--|
| EXTERNAL DIMENSIONAL DATA    |                       |  |
| Width Overall                | 27 1⁄4"               |  |
| Depth Overall with Handles   | 29 1⁄8"               |  |
| Height Overall               | 72 ¾"                 |  |
| Number of Doors              | 2                     |  |
| Depth with Door Open 90°     | 52 <sup>13</sup> ⁄16" |  |
| Door Openings (in)           | 24" x 24 ¾"           |  |
| INTERNAL DIMENSIONAL DATA    |                       |  |
| NET Capacity (cubic ft.)     | 16.85                 |  |
| Internal Width Overall (in)  | 24 1/4"               |  |
| Internal Depth Overall (in)  | 23 1/8"               |  |
| Internal Height Overall (in) | Max 53"<br>Min 46 %"  |  |
| Number of Shelves            | 5                     |  |
| ELECTRICAL DATA              |                       |  |
| Full Load Amperes            | 5.5                   |  |
| Voltage                      | 115/60/1              |  |
| Nema PLug (8' cord)          | 5-15P                 |  |
| REFRIGERATION DATA           |                       |  |
| Horsepower                   | 1/4                   |  |
| Capacity (BTU/Hr)            | 1997                  |  |
| Heat Rejection (BTU/Hr)      | 2995.5                |  |
| Charge (lbs/grams/ounce)     | 0.1875 / 85 / 3.0     |  |
| SHIPPING DATA                |                       |  |
| Gross Weight (crated lbs)    | 328 lbs               |  |
| Height - Crated              | 76"                   |  |
| Width - Crated               | 30"                   |  |
| Depth - Crated               | 32"                   |  |

\*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

# Bottom Mount Reach-In Half-Solid Door Model: RI18HC-HS





## **ELECTRICAL CONNECTION**



Unit pre-wired at factory and include 10.7' long cord and plug set.

