

| PROJECT: | | | | |
|-----------------|-----------|--|--|--|
| MODEL #: | | | | |
| ITEM #: | QTY: | | | |
| AVAILABLE W/H : | APPROVAL: | | | |

Mega Top Sandwich Prep Tables









STANDARD FEATURES

Cabinet construction

- Stainless steel cabinet construction Stainless steel interior and exterior (galvanized steel back & bottom).
- Cycolpentane Insulation Contains no hydro-fluorocarbons (HFCs) and is environmentally friendly
- Drop-in section:
 Fans force cold air into this enclosed area keeping stored food items consistently cold
- Insulated pan cover with a stainless steel divider which prevents food spillage into the storage area beneath
- Standard 1/6 / 4" food pans are provided. Unit accommodates 6" deep pans
- Epoxy coated wire shelves with adjustable shelving height.
- Side rail cutting board bracket with 9 ½" deep, 1/2" thick cutting board included
- Four (4) 4" diameter swivel casters with front brakes standard.

Refrigeration

- Hydrocarbon refrigerants (R-290) increases energy efficiency by up to 25% compared to using HFC refrigerants. It is safer for the environment and does not cause ozone depletion.
- Self-contained system, rear mounted compressor.
- Electrodeposition coated evaporator increases performance by maintaining the heat transfer rates over the life of the evaporator and reducing potential corrosion.
- Innovative hot gas frame heating system reduces condensation and increases energy efficiency.
- Refrigerators have a temperature range between 33°F ~ 39°F

Doors

- Self closing doors
- Durable door gasket with easy replacement.
- Lifetime guaranteed heavy duty all metal door handles. (Ni-Cr Plated)

Design

- Self-diagnostic digital temperature control & monitor system
 Digital display allows for easy monitoring
 Digital controls include automatic evaporator
- Rounded corner design gives a stylish appearance and reduces chances of injury.
- Visual and audible door open alarm, alarm sounds when doors are not completely closed to protect against food spoilage
- Standard NSF/ANSI Standard 7 compliant

Connection

fan motor delav.

• 9 ft long flexible three wire cord with molded plug

Optional Features & Accessories

- 2.5" diameter casters available
- 6" adjustable feet available
- Additional shelves are available.
- Drawer models available
- 6" pans available

WARRANTY APPROVALS: AVAILABLE AT:


3 Years Parts and Labor


5 Years on Compressor in USA


Mega Top Sandwich Prep Tables


PRODUCT PLAN VIEW


- Top View -












- Front View -









BLMT28-HC


BLMT36-HC

BLMT48-HC

BLMT60-HC

BLMT72-HC

Pan Configuration








- Side View -

BLMT28-HC







BLMT60-HC

BLMT72-HC

PRODUCT SPECIFICATION

Mega Top Sandwich Prep Tables

| Model | Product Description | | | | Refrigerant | Temperature Range | | Easy Maintenance | | | Cord Length (ft/m) | |
|-----------|-------------------------------|----------------------|---------|----------------------------------|------------------|-------------------|---------|-------------------------|------|-------------------|--------------------|-------------|
| | Mega Top Sandwich Prep Tables | | | | R-290 | 33°F ~ 39°F | | Sliding Condensing Unit | | | 9.8ft (3m) | |
| | Doors | Capacity (Cu.Ft.) | Shelves | Cabinet Dimensions (inches / mm) | | | Voltage | Δ | NEMA | Weight (lbs / kg) | | |
| | | | | Г | D | Н | пР | voitage | Amps | config. | Net Weight | Ship Weight |
| BLMT28-HC | 1 | 7 | 1 | 27 1/2" (699mm) | 37 9/32" (947mm) | 44 1/4" (1122mm) | 1/4+ | 115V / 60Hz | 4.1 | NEMA 5-15 | 161 (73) | 203 (92) |
| BLMT36-HC | 2 | 9.5 | 2 | 36 3/8" (923mm) | 37 9/32" (947mm) | 44 1/4" (1122mm) | 1/4+ | 115V / 60Hz | 4.1 | NEMA 5-15 | 190 (86) | 234 (106) |
| BLMT48-HC | 2 | 13.1 | 2 | 48 3/8" (1227mm) | 37 9/32" (947mm) | 44 1/4" (1122mm) | 1/4+ | 115V / 60Hz | 4.7 | NEMA 5-15 | 227 (103) | 289 (131) |
| BLMT60-HC | 2 | 16.7 | 2 | 60 3/8" (1533mm) | 37 9/32" (947mm) | 44 1/4" (1122mm) | 1/4+ | 115V / 60Hz | 4.9 | NEMA 5-15 | 276 (125) | 340 (154) |
| BLMT72-HC | 3 | 20.2 | 3 | 72 3/8" (1839mm) | 37 9/32" (947mm) | 44 1/4" (1122mm) | 1/4+ | 115V / 60Hz | 5.4 | NEMA 5-15 | 311 (141) | 390 (177) |

*BLUE AIR has the right to change specifications without further notice.

