

PROJECT:							
MODEL #:							
ITEM #:		QTY:					
AVAILABLE W/H :	APPROVAL:						

## **Chest Freezer**



# STANDARD FEATURES

### Cabinet construction

- Painted Galvanized Steel Exterior to minimize dents, scratches and rust
- Epoxy coated wire baskets to minimize peeling and rust
- Polyurethane insulation CFC free, high density insulation foam which is eco friendly and energy efficient
- Bottom drain with plug for easy cleaning
- Sliding door lock with keys with additional security
- Four (4) standard casters

### Refrigeration

- Hydrocarbon refrigerants (R-290) increases energy efficiency by up to 25% compared to using HFC refrigerants. It is safer for the environment and does not cause ozone depletion
- Bottom mount compressor system The bottom mounted compressor provides quick and easy maintenance
- $\bullet$  Chest freezer has a temperature range between -10°F ~ 0°F

### Design & Features

- Digital Temperature control for reliable temperature operation
- Treated curved glass sliding door to enhance cooling
- Anti-fog tempered glass provides a clear view of the interior

### Lighting

LED Interior lighting.

#### Standard

• ETL Safety and ETL Sanitation certification


### Connection


• 115V/60hz NEMA 5-20 plug configuration

# **Chest Freezer**


# PRODUCT PLAN VIEW

- Top View -






- Front View -




**BCF56-HC** 



BCF80-HC

- Side View -



# PRODUCT SPECIFICATION

Freezer

Model	Product Description				Refrigerant	Temperature Range		Easy Maintenance			Cord Length (ft/m)	
	Chest Freezer				R-290	-10°F ~ 0°F		Sliding Condensing Unit			9.8ft (3m)	
	Doors	Capacity (Cu.Ft.)	Basket	Cabi	net Dimensions (inches	nes / mm)		LID Valtage	Λ	NEMA	Weight (lbs / kg)	
				L	D	Н	пР	Voltage	Amps	config.	Net Weight	Ship Weight
BCF56-HC	2	17.66	4	56 1/8" (1426mm)	29 5/8" (752mm)	33 1/8" (841mm)	1/2	115V / 60Hz	2.4	NEMA 5-20	170 (77)	223 (101)
BCF80-HC	2	24.72	6	79 3/4" (2026mm)	29 5/8" (752mm)	33 1/8" (841mm)	3/4	115V / 60Hz	3.8	NEMA 5-20	256 (116)	311 (141)

\*BLUE AIR has the right to change specifications without further notice.

