ICB-DV, TALL

Height: 35.0" Width: 10.2" Depth: 22.0" (88.9cm) (25.9cm) (55.9cm)





- Sleek modernized design language, with rounded angles on the corners and trunk
- Digital readout displays in English, Spanish, or French ---for easier programming and control--- and can show either 'Standard' or Metric measurements. Digital readout also shows machine status, and targeted advertising messages can be programmed for display.
- BUNN Infusion Series technology allows for multiple recipes from one footprint --with three brew buttons and two batch sizes
- Includes overlay kit for customization of brewer interface
- Energy-saver mode reduces tank temperature during idle periods
- The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- USB programming capable
- Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing.
- Hot water faucet (supplied for custom installation)
- Dual voltage adaptable (Can operate at 120V/15 amp or 120/208-240V/20 amp)

Agency:





Specifications

Product #: 53100.0001 Funnel: Black Plastic Smart Funnel

Water Access: Plumbed Interface: Wireless

Finish: Stainless

Additional Features

BrewWISE

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz
120	14	1700	Yes	NEMA 5-15P	-	60°F (15.5°C)	1	2	60
120/208	14	2900	-	N/A	-	60°F (15.5°C)	1	3	60
120/240	17	4050	-	N/A	-	60°F (15.5°C)	1	3	60

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratinos.

Plumbing Requirements

	· · · · · · · · · · · · · · · · · · ·						
PSI		kPa	Fitting Supplied	Water Flow Required (GPM)			
	20-90	138-621	3/8" Male Flare Fitting	1.00			


CAD Drawings

2D	Revit	KLC
•		

WARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.



Unit				Shipping					
	Height	Width	Depth	Height	Width	Depth	Weight	Volume	
English	35.0 in.	10.2 in.	22.0 in.	-	-	-	47.860 lbs	-	
Metric	88.9 cm	25.9 cm	55.9 cm	-	-	-	21.709 kgs	-	



Related Products & Accessories:ICB-DV, TALL(53100.0001)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000





Serving & Holding Options: ICB-DV, TALL(53100.0001)



TF SERVER, 1G DSG GEN3

Product #:42700.0200



TF SERVER, 1.5G DSG GEN3

Product #:42750.0200



TF SERVER, 1G MECH GEN3

Product #:44000.0200



TF SERVER, 1.5G MECH GEN3

Product #:44050.0200

STAND ASSY, TF SERVER

Product #:54473.0000



