

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

UC-48F-A 48" ADA Height Undercounter Work Top Freezer - 12 Cu. Ft.



FEATURES

- · Stainless steel exterior and interior
- Refrigeration system keeps food at safe temperatures
- · Self-closing doors with 90 degree stay-open feature
- · Adjustable heavy-duty PVC coated shelves
- · Recessed door handle
- Electronic control system
- · Preinstalled heavy-duty casters with brakes
- Removable installation board
- · Hydro-Carbon R290 refrigerant
- · ADA compliant working height
- 4" backsplash optional

This Coldline commercial undercounter freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- ETL Sanitation Listed





SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	47.2″W x 29.5″D x 35.5″H
ADA Height Dimensions	47.2″W x 29.5″D x 33.5″H
Interior Dimensions	42.5″W x 22.9″D x 23.5″H
Packaging Dimensions	50"W x 32.3"D x 38.5"H
Working Height	33.5"
Net Volume	12 cu. ft.
Unit Weight	214 lb.
Shipping Weight	275 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.5
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING

Temperature Range	-8°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4+

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 20.8"W x 17.1"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: UC-48F-A **NEMA 5-15P**

