

Project: Quantity: Model #: Approval:

For Commercial Use Only

### C-3FE 81" Three Solid Door Reach-In Freezer



#### **FEATURES**

- · Stainless steel interior and exterior
- Aluminum back
- · Refrigeration system keeps food at safe temperatures
- · Self-closing doors with 90 degree stay-open feature
- · Locks and keys included
- · Adjustable heavy-duty PVC coated shelves
- · Recessed door handle
- · Electronic control system
- · Preinstalled heavy-duty casters with brakes
- · Removable installation board
- · Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- **ETL Sanitation Listed** Certified to NSF Standard





SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Page 72



# Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

### **TECHNICAL DATA**

#### **DIMENSIONS**

Exterior Dimensions	80.9"W x 32.2"D x 81.5"H
Interior Dimensions	76.3"W x 27"D x 59.5"H
Packaging Dimensions	83.3"W x 34"D x 84.5"H
Net Volume	66.5 cu. ft.
Unit Weight	542 lb.
Shipping Weight	635 lb.

#### **ELECTRICAL**

Voltage	115
Hertz	60
Phase	1
Amps	12
Plug Type	NEMA 5-20P
Power Cord Length	96"

#### **COOLING**


Temperature Range	-8°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1-1/2


#### **CONSTRUCTION**


Exterior Material	430 Stainless Steel
Interior Material	430 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	6 Qty: 23.6"W x 23.2"D
	3 Qty: 25.1"W x 23.2"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	90 lb.
Adjustable Shelf	Yes
Interior Light	Yes
-	

## **TECHNICAL DRAWING**









Page 73