

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

### CBB-60G-T 60" Underbar Height Swing Glass Door Back Bar Cooler, Black



### **FEATURES**

- · Durable S/S interior walls, floor and ceiling
- · Vinyl on steel in black finish exterior
- Refrigeration system keeps food at safe temperatures
- · Electronic control system
- · Adjustable heavy-duty PVC coated shelves
- Self-closing doors with locks
- · Swing doors
- Narrow depth
- · LED interior lighting
- · Removable installation board
- · Pull out door handle
- · Hydro-Carbon R290 refrigerant

This Coldline commercial back bar cooler is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- ETL Sanitation Listed



SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

# **TECHNICAL DATA**

#### **DIMENSIONS**

Exterior Dimensions	60"W x 23.62"D x 34.25"H
Interior Dimensions	48″W x 20″D x 31″H
Packaging Dimensions	63″W x 27.5″D x 41.75″H
Product Capacity	(2) ½ kegs
Net Volume	17.3 cu. ft.
Unit Weight	276 lb.
Shipping Weight	319 lb.

#### **ELECTRICAL**

Voltage	115
Hertz	60
Phase	1
Amps	2.88
Plug Type	NEMA 5-15P
Power Cord Length	84"

#### **COOLING**

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/5

#### **CONSTRUCTION**

Exterior Material	Coated Steel+Galvanize Top
Exterior Color	Black
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Swing
Door Type	Glass
Shelf Size	(4) Qty: 23.6"W x 18"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	L.E.D

# **TECHNICAL DRAWING**

MODEL: CBB-60G-T



**NEMA 5-15P** 





