

### Coldline D4-B 98" Four Glass Door Merchandiser Freezer with LED Lighting, Black



#### FEATURES

- 98" black swing glass door merchandiser freezer
- Four Low-E double pane thermal insulated glass doors
- Easy to use digital temperature controls
- High-density polyurethane insulation preserves cold air
- Temperature range: -8 to 1 degrees F
- 5 vertical brilliant LED lights
- Independent LED switch
- Ergonomic door handles
- Magnetic door gasket
- Automatic defrost
- 16 heavy-duty, adjustable PVC-coated shelves
- 10 Pre-installed low-profile casters, 2 leveling feet
- Anti-fogging tempered self-closing glass doors
- Bottom mounted refrigeration system
- 90" length power cord, NEMA 5-15P plug



CE

USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

### TECHNICAL DATA

#### DIMENSIONS

Exterior Dimensions	98.43"W x 28.35"D x 80.51"H
Interior Dimensions	93.7"W x 22.8"D x 60.4"H
Packaging Dimensions	100.7"W x 30.7"D x 83"H
Net Volume	69 cu. ft.
Unit Weight	695 lb.
Shipping Weight	834 lb.

#### ELECTRICAL

Voltage	110
Hertz	60
Phase	1
Amps	15
Plug Type	NEMA 5-15P
Power Cord Length	90"

#### COOLING

Temperature Range	32°F to 41°F
Refrigerant	R290
Max. Ambient Temp	100°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	(2) 3/4

#### CONSTRUCTION

Exterior Material	Coated Steel
Exterior Color	Black
Interior Material	Coated Steel
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Swing
Door Type	Glass
Shelf Size	(8) 21.7"W x 20.35"D (8) 24.2"W x 20.35"D
Shelf Load Capacity	100 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	(5) L.E.D
Mobility Wheels/Casters	10 Pre-installed Casters, 2 Leveling Feet

### TECHNICAL DRAWING

MODEL: D4-B

MFR ITEM #:



NEMA 5-15P

