

Coldline G48S-B 48" Double Glass Sliding Door Merchandiser Refrigerator with LED Lighting, Black



FEATURES

- 48.03" black sliding glass door merchandiser refrigerator
- 2 double pane sliding glass doors
- Easy to use digital temperature controls
- High-density polyurethane insulation preserves cold air
- Temperature range: 32-41 degrees F
- Brilliant LED lights
- Independent LED switch
- LED lighted top panel
- Automatic defrost
- Magnetic door gasket
- 8 heavy-duty, adjustable PVC-coated shelves
- 4 pre-installed low-profile casters, 2 with brakes
- Hydro-Carbon R290 refrigerant
- Self-closing glass doors
- Bottom mounted refrigeration system
- 90" length power cord, NEMA 5-15P plug

- cETLus Listed
 - ETL Sanitation Listed
- Certified to NSF Standard



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	48.03"W x 26.18"D x 83.46"H
Interior Dimensions	44.65"W x 21.47"D x 65.35"H
Packaging Dimensions	50.4"W x 29.2"D x 87.8"H
Net Volume	30 cu. ft
Unit Weight	408 lb.
Shipping Weight	452 lb.

ELECTRICAL

Voltage	110
Hertz	60
Phase	1
Amps	5.97
Plug Type	NEMA 5-15P
Power Cord Length	90"

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4

CONSTRUCTION

Exterior Material	Coated Steel
Exterior Color	Black
Interior Material	PCM
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Sliding
Door Type	Glass
Shelf Size	(8) 21.50"W x 18.81"D
Shelf Load Capacity	66 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	L.E.D
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: G48S-B

MFR ITEM #: LGF-1000S



NEMA 5-15P

