

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

UCN-48R 48" Narrow Depth Undercounter Worktop Refrigerator



FEATURES

- Narrow 24" depth undercounter refrigerator
- Stainless steel exterior and interior
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with stay-open feature
- Adjustable heavy-duty PVC coated shelves
- Recessed door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Hydro-Carbon R290 refrigerant
- 4" backsplash optional

The Coldline UCN 48" is a great refrigerator for an undercounter or worktop application. Interior and exterior made of stainless steel. Wheels, adjustable shelves, and self-closing doors come standard on all units. Eco-friendly R290 refrigeration system maintains 33 to 41 degree temperature to keep your food in the safe zone.

USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	48.4"W x 24"D x 38.2"H
Interior Dimensions	47.7"W x 18.6"D x 29.1"H
Packaging Dimensions	50.4"W x 28.9"D x 40.7"H
Working Height	38.2"
Net Volume	7 cu. ft.
Unit Weight	165 lb.
Shipping Weight	196 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.3
Plug Type	NEMA 5-15P
Power Cord Length	96"

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	104°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 17.5"W x 9"D
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: UCN-48R

MFR ITFM #:



NEMA 5-15P

