

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

XS251S 32 " Curved Glass Top Display Ice Cream Freezer

FEATURES

- ▶ Holds Temperature Between -13°F To 0°F
- ▶ Curved Glass Top Lid With Sliding Doors
- ▶ White Powder Coated Steel Exterior
- ▶ Embossed Aluminum Interior
- ▶ Preinstalled Low Profile Casters With Brakes
- ▶ Drain Plug For Manual Defrosting
- ▶ Coated Wire Baskets Included
- ▶ Hydro-Carbon R290 Refrigerant

This Coldline curved glass top ice cream display freezer is designed to boost your impulse sales of ice cream, popsicles, pints of sorbet, and frozen appetizers. It features a high-efficiency refrigeration system, a durable stainless steel design, and a high-accessibility curved glass top display. Built for school concession stands, diners, and convenience stores, this ice cream display machine keeps top-selling frozen novelties within easy reach to boost selling potential.



- ▶ ETL Certified
- ▶ ETL Sanitation
- ▶ NSF Compliant



WARRANTY

Coldline products are backed by a 1 Year / 5 Year limited manufacturer warranty. The unit itself and parts within are guaranteed against manufacturing defects for a period of 1 year. The compressor is guaranteed for an additional 4 years. Extended warranty is available. Glass, due to its fragile nature, is not included under warranty coverage. Always inspect your delivery for freight damage before you accept it. Freight damage will not be considered a manufacturing defect and should be refused or remedied through a claim with the carrier.



Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	31.5"L x 27.3"D x 34.5"H
Interior Dimensions	27"L x 22"D x 27"H
Packaging Dimensions	32.75"L x 29.75"D x 37"H
Net Volume	7 cu. ft.
Unit Weight	115 lb.
Shipping Weight	137 lb.

ELECTRICAL

Voltage	110
Hertz	60
Phase	1
Amps	2.5
Wattage	168
Kilowatt-Hour	1.812
Plug Type	NEMA 5-15P
Power Cord Length	72"

COOLING

Temperature Range	-13°F - 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Manual
Temperature Controller	Manual
Horsepower	1/5

CONSTRUCTION

Exterior Material	White Powder Coated Steel
Interior Material	Embossed Aluminum
Insulation Material	Foamed-in-Place Polyurethane
Baskets	3 Qty: 21"L x 8.5"D x 10.5"H
Basket Material	Coated Wire
Drain Plug Location	Right Side

DIAGRAM

MODEL: XS251S

MFR MODEL:

