

## **Datasheet**

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

# XS551S 60 " Curved Glass Top Display Ice Cream Freezer



#### **FEATURES**

- ▶ Holds Temperature Between -13°F To 0°F
- ▶ Curved Glass Top Lid With Sliding Doors
- White Powder Coated Steel Exterior
- ▶ Embossed Aluminum Interior
- Preinstalled Low Profile Casters With Brakes
- Drain Plug For Manual Defrosting
- ▶ Coated Wire Baskets Included
- ▶ Hydro-Carbon R290 Refrigerant

This Coldline curved glass top ice cream display freezer is designed to boost your impulse sales of ice cream, popsicles, pints of sorbet, and frozen appetizers. It features a highefficiency refrigeration system, a durable stainless steel design, and a high-accessibility curved glass top display. Built for school concession stands, diners, and convenience stores, this ice cream display machine keeps top-selling frozen novelties within easy reach to boost selling potential.

- ▶ ETL Certified
- ▶ ETL Sanitation
- ▶ NSF Compliant







### WARRANTY

Coldline products are backed by a 1 Year / 5 Year limited manufacturer warranty. The unit itself and parts within are guaranteed against manufacturing defects for a period of 1 year. The compressor is guaranteed for an additional

4 years. Extended warranty is available. Glass, due to its fragile nature, is not included under warranty coverage. Always inspect your delivery for freight damage before you accept it. Freight damage will not be considered a manufacturing defect and should be refused or remedied through a claim with the carrier.





**US Restaurant Group, Inc.** 

Rev. 9-2018

Phone: 800-764-1172 | www.usrestaurant.com | sales@usrestaurant.com



# **Datasheet**

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

# **TECHNICAL DATA**

#### **DIMENSIONS**

Exterior Dimensions	60.2"L x 27.3"D x 34.5"H
Interior Dimensions	55"L x 22"D x 27"H
Packaging Dimensions	61.75"L x 29.75"D x 37"H
Net Volume	14 cu. ft.
Unit Weight	176 lb.
Shipping Weight	210 lb.

#### **ELECTRICAL**

Voltage	110
Hertz	60
Phase	1
Amps	2.9
Wattage	249
Kilowatt-Hour	2.340
Plug Type	NEMA 5-15P
Power Cord Length	72"

#### **COOLING**

Temperature Range	-13°F - 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Manual
Temperature Controller	Manual
Horsepower	1/3

#### CONSTRUCTION

Exterior Material	White Powder Coated Steel
Interior Material	Embossed Aluminum
Insulation Material	Foamed-in-Place Polyurethane
Baskets	6 Qty: 21"L x 8.5"D x 10.5"H
Basket Material	Coated Wire
Drain Plug Location	Right Side

## **DIAGRAM**





