



For questions or ordering info:
 Phone: (917) 525-2066
 Email: support@kitchenall.com
 Web: www.kitchenall.com

Kitchenall
 New Restaurant Equipment

Refrigerated Insulated Employee Service Salad Bar



48" MODEL PICTURED



PRODUCT HIGHLIGHTS

- LED Interior Lighting
- Holds 36°F ~ 41°F
- Defrost Timer System
- ETL UL Certified
- Stainless Steel Front, Top and Sides
- Aluminum Sides & Top with Stainless Steel Floor
- CFC- Free Polyurethane Foam Cell Insulation
- Self Closing Door
- Adjustable Wire Shelves
- Insulated Front Slanted Sneezeguard
- Sliding Rear Door for Top Access
- Swinging Rear Door for Bottom Access
- 5" Casters Standard



Don't see the size that you're looking for? We can customize it!

MODEL	WXDXH	DOORS	SHELF	VOLTS	H.P.	FITS 1/6 PAN	CUFT (BOTTOMSECTION)	WEIGHT
SBC36	36X32X53	1 1/2	1	115	1/4	12	12.2	188
SBC48	48X32X53	1 1/2	1	115	1/4	18	16.2	200
SBC60	60X32X53	1 1/2	1	115	1/3	24	20.3	260
SBC72	72X32X53	2 1/2	3	115	1/3	30	26.2	330
SBC84	84X32X53	2 1/2	3	115	1/3	36	30.3	370
SBC96	96X32X53	3 1/2	3	115	1/2	42	36.2	410
SBC118	120X32X53	4 1/2	4	115	3/4	54	46.1	485

Additional Features:

- Our defrost timer system keeps cooling systems separate from the evaporator. It doesn't ice up or inhibit the compressor, giving the unit outstanding performance and a longer life even in the most difficult environments.
- These models are designed to operate in an environment where temperature and humidity do not exceed 75°F and 65% relative humidity.

Revised: 12/14/17

Specifications subject to change without notice.