

**219766 (ECOE202T3L30)**

SkyLine PremiumS Combi Boiler Oven with touch screen control, 20x2/1GN, electric, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, spray gun, 6-sensor probe, boiler in AISI 316L, 3-glass door and IoT module - 2080V US

## Description

\*\*Replaces 219755

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor.
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 4 automatic cycles (short, medium, intensive, rinse) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, remote software update, HACCP, recipe and energy management (optional)
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Stainless steel construction throughout
- Supplied with n.1 trolley rack 2/1 GN, 2 1/2 inches pitch.
- Adjustable levelling feet



## Main Features

- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- Dry, hot convection cycle (77 °F - 575 °F/25 °C - 300 °C): ideal for convection cooking.
- Combi cycle (77 °F - 575 °F/25 °C - 300 °C): The combination of hot air and steam creating a humidity controlled cooking environment, to reduce the cooking process times and food weight loss.
- Steam cycle (213°F - 266°F/101 °C - 130°C): Ideal for sous vide, re-thermalization, and Low Steaming of food and vegetables
- Built-in steam generator: Boiler in AISI 316 steel for highly precise humidity and temperature control according to the chosen settings.
- Lambda Sensor: Real humidity control of +-1% for automatic quantity and size of food recognition to guarantee consistent cooking results
- Reversible Fan: 7 speed fan levels from 300 to 1500 RPM with reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Automatic cool-down and pre-heat function
- MultiTimer: Special feature to manage up to 60 different cooking cycles at the same time in the same cavity guaranteeing even cooking results. Up to 200 MultiTimer available programs
- Automatic Cooking Mode: includes 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, pastries and sweet bakery, bread, dessert) with 100+ different pre-installed variations. The Automatic Sensory Phase of the oven optimizes the cooking process according to the size, quantity and type of food loaded in the oven. Real-time monitoring of cooking parameters. Personalize and save up to 70 variations per food family.
- Cycles+: Regeneration (ideal for banqueting on plate or rethermalizing on tray)CHAR(10)-Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related familyCHAR(10)- Proving cycleCHAR(10)- EcoDelta cooking, cooking with the difference between the food probe core temperature of the food and the cooking cavityCHAR(10)- Sous-vide cookingCHAR(10)- Static Combi (to reproduce traditional cooking from static oven)CHAR(10)- Pasteurization of pastaCHAR(10)- Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood)CHAR(10)-Food safe Control and Advanced Food Safe Control: to automatically monitor safely the cooking process in compliance with HACCP hygienic standards or drive cooking with pasteurization factor Patented US6818865B2 and related familyCHAR(10)CHAR(10)
- Back-up mode: self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- OptiFlow: air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.

## Construction

- 304 AISI stainless steel construction throughout.
- IPX 5 spray water protection certification for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- Boiler in 316L to protect against corrosion.
- Integrated spray gun with automatic retracting system for fast rinsing.
- Triple thermo-glazed door: with 2 hinged inside panels for easy cleaning and double LED lights line.
- Front access to control board for easy service.



---

## User Interface & Data Management

---

- Picture Management: upload full customized images of cooking cycles or food items
- e-learning: equipment trainings, how-to guides, and technical documentation easily accessible by scanning QR-Code with any mobile device.
- Make-it-mine: feature to allow full personalization or locking of the user interface by selecting what is visible on screen
- SkyDuo: Oven and Blast Chiller automatic communication to guide the user through the cook&chill process by creating a safe controlled environment to optimize time and efficiency (requires optional accessory).
- SkyHub: customizable homepage to allow the user to group their favorite functions for immediate access when operating.
- MyPlanner: on-screen agenda where the user can plan their daily work, set reminders for several users and receive personalized alerts for each activity
- USB port: to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Touchscreen: High resolution interface (translated into more than 30 languages including Spanish and French) - color-blind friendly panel.
- Data Analytics: automatic consumption visualization at the end of the cycle.
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).

---

## Sustainability

---

- Energy Star 2.0 certified product
- Reduced-Power Feature: To consume less energy during customized slow cooking cycles.
- Plan-n-Save: the oven organizes the sequence of the chosen cooking cycles to optimize the processes in the kitchen reducing time and energy consumption.
- Door handle: ergonomic wing-shaped design for hands-free door opening with elbow, to allow simple trays management (Registered Design at EPO EM003143551).
- Zero Waste: library of Automatic recipes that aims to provide sustainability recipes to repurpose raw food close to expiration date (e.g.: from milk to yogurt) • obtain genuine and tasty dishes from overripe fruit/vegetables (usually considered not appropriate for sale) • promote the use of typically discarded food items (e.g.: carrot peels).
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.
- Sustainability: The outer cardboard packaging is made from 70% recycled materials and FSC\*-certified paper, printed with eco-friendly, water-based ink to support sustainability and environmental responsibility (\*Forest Stewardship Council is the world's leading organization for sustainable forest management).
- Triple-glass door minimize your energy loss.\* \*Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20



# Technical specifications

## Electric

|                            |                  |
|----------------------------|------------------|
| Supply voltage:            | 208 V/3 ph/60 Hz |
| Rated amps:                | 180.1 A          |
| Electrical power max:      | 65.4 kW          |
| Plug type:                 | Without cable    |
| Electrical power, default: | 65.4 kW          |

## Water:

|                              |                     |
|------------------------------|---------------------|
| Pressure:                    | 15-87 psi (1-6 bar) |
| Chlorides:                   | <85 ppm             |
| Conductivity:                | >50 µS/cm           |
| Drain "D":                   | 50mm                |
| Water inlet "CW" connection: | 3/4"                |
| Pressure, bar min/max:       | 1-6 bar             |

## Capacity:

|                    |             |
|--------------------|-------------|
| Tray type:         | 20 - GN 2/1 |
| Max load capacity: | 200 kg      |
| Shelf capacity:    | 20 Grids    |


## Key Information:

|                              |                                                                     |
|------------------------------|---------------------------------------------------------------------|
| External dimensions, Width:  | 45 3/4" (1162 mm)                                                   |
| External dimensions, Depth:  | 42" (1066 mm)                                                       |
| External dimensions, height: | 70 5/8" (1794 mm)                                                   |
| Net weight:                  | 815 lbs (369.5 kg)                                                  |
| Shipping width:              | 47 3/16" (1200 mm)                                                  |
| Shipping depth:              | 45 3/8" (1150 mm)                                                   |
| Shipping height:             | 79 1/32" (2010 mm)                                                  |
| Shipping weight:             | 1047 lbs (407.5 kg)                                                 |
| Shipping volume:             | 97.81 ft³ (2.77 m³)                                                 |
| Approvals                    | ETL C&US;ENERGY STAR;ETL SANITATION;ErgoCert 4*;UL verified V689870 |


## Sustainability

|                      |            |
|----------------------|------------|
| Current consumption: | 180.1 Amps |
| Water consumption:   | 33.3 lt/hr |


## Front



## Side



## Top



CW11 = Cold Water inlet 1 (cleaning)

D = Drain

EI = Electrical inlet (power)

DO = Overflow drain pipe



Find out more:  
ISO Certificates  
Electrolux Professional Recognitions

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/09/11

4/7

# Technical specifications

## Included Accessories

| PNC Code | Description                                                                               | Quantity |
|----------|-------------------------------------------------------------------------------------------|----------|
| 922076   | Aisi 304 stainless steel grid (18" x 26")                                                 | 10       |
| 922757   | 20 Tray Rack Trolley, Full Sheet Pans, 2 ½" (63mm) pitch for 202 ovens and blast chillers | 1        |

## Optional Accessories

| PNC Code | Description |
|----------|-------------|
|----------|-------------|

### Cleaning Solutions

|        |                                                     |
|--------|-----------------------------------------------------|
| 922386 | HOLDER FOR DETERGENT TANK - WALL MOUNTED            |
| 922618 | External connection kit for detergent and rinse aid |

### [NOT TRANSLATED] Connectivity

|        |                                                         |
|--------|---------------------------------------------------------|
| 922421 | IoT module for SkyLine ovens and blast chiller/freezers |
| 922435 | Connectivity router (WiFi and LAN)                      |

### Containers, Trays and Grids

|        |                                                                       |
|--------|-----------------------------------------------------------------------|
| 922017 | Pair of half size oven racks, type 304 stainless steel                |
| 922036 | Chicken racks, pair (2) (fits 8 chickens per rack)                    |
| 922062 | Single 304 stainless steel grid (12" x 20")                           |
| 922189 | Baguette tray, made of perforated aluminum, silicon coated, 16" x 24" |
| 922190 | Perforated baking tray, made of perforated aluminum, 16" x 24"        |
| 922191 | Baking tray, made of aluminum 16" x 24"                               |
| 922239 | Pair of frying baskets                                                |
| 922264 | Pastry grid 16" x 24"                                                 |
| 922266 | Grid for whole chicken 1/1GN (8 per grid - 2.6 lbs each)              |
| 922348 | Multipurpose hook                                                     |
| 922362 | Grid for 8 whole ducks (1.8KG, 4LBS) - GN 1/1                         |
| 922651 | Dehydration tray, (12" x 20"), H=2/3"                                 |
| 922652 | Flat dehydration tray, (12" x 20")                                    |
| 922713 | Mesh grilling grid (12" x 20")                                        |
| 922746 | Tray for traditional static cooking, H=100mm (12" x 20")              |
| 922747 | Double-face griddle, one side ribbed and one side smooth, 400x600mm   |
| 925001 | Non-stick universal pan (12" x 20" x 1 1/2")                          |
| 925002 | Non-stick universal pan (12" x 20" x 2 1/2")                          |
| 925003 | Frying griddle double sided (ribbed/smooth) 12" x 20"                 |



Find out more:  
ISO Certificates  
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/09/11

5/7

# Technical specifications

| PNC Code                           | Description                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------|
| <b>Containers, Trays and Grids</b> |                                                                                             |
| 925004                             | Aluminum combi oven grill (12" x 20")                                                       |
| 925005                             | Egg fryer for 8 eggs (12" X 20")                                                            |
| 925006                             | Flat baking tray with 2 edges (12" x 20")                                                   |
| 925008                             | Potato baker GN 1/1 for 28 potatoes (12"X20")                                               |
| 925012                             | 6 NON-STICK U-PAN (12" X 20" X 3/4")                                                        |
| 925013                             | 6 NON-STICK U-PAN (12"X20"X1 1/2")                                                          |
| 925014                             | 6 NON-STICK U-PAN (12"X20"X2 1/2")                                                          |
| <b>Drains</b>                      |                                                                                             |
| 922738                             | Stainless steel drain kit for 201 & 202 oven, d=50mm (2")                                   |
| <b>Feet, Wheels and Ramps</b>      |                                                                                             |
| 922688                             | 4 adjustable feet for 61,62 & 101,102 combi ovens, 100-115mm (5 9/10in -7 9/1in)            |
| 922707                             | 4 flanged feet for 201 and 202 combi ovens , 2", 100-130mm (4"-5")                          |
| 922716                             | Levelling entry ramp for 202 combi oven                                                     |
| <b>Food Probes</b>                 |                                                                                             |
| 922281                             | USB Probe for sous-vide cooking (only for Touchline ovens)                                  |
| 922390                             | USB SINGLE POINT PROBE                                                                      |
| 922714                             | Probe holder for liquids                                                                    |
| <b>Grease/Oil Management</b>       |                                                                                             |
| 922357                             | Grease collection tray (2 2/5") for 62 and 102 ovens                                        |
| <b>Handling - Bakery</b>           |                                                                                             |
| 922762                             | BAKERY/PASTRY TROLLEY FOR 20 GN 2/1 OVEN - 16 RACKS 400X600MM - 80MM PITCH                  |
| <b>Handling - Banqueting</b>       |                                                                                             |
| 922367                             | Thermal blanket for 202 oven (trolley not included)                                         |
| 922760                             | 202 Banquet trolley for oven and blast chiller for 92 plates holding , 3.3" (85mm) pitch    |
| 922764                             | 201 Banquet trolley for combi and blast chiller for 116 plates holding, 2.5" 66mm pitch     |
| <b>Handling - Gastronorm</b>       |                                                                                             |
| 922686                             | Trolley with tray rack, 202 combi oven, h=85mm (3 1/3")                                     |
| 922757                             | 20 Tray Rack Trolley, Full Sheet Pans, 2 1/2" (63mm) pitch for 202 ovens and blast chillers |
| 922758                             | 16 Tray Rack Trolley, Full Sheet Pans, 3" (80mm) pitch for 202 ovens and blast chillers     |



Find out more:  
ISO Certificates  
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/09/11

6/7

# Technical specifications

| PNC Code                              | Description                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------|
| <b>Installation Solutions</b>         |                                                                                                            |
| 922658                                | Heat shield for 202 combi oven                                                                             |
| 922739                                | Plastic drain kit for 201 & 202 combi oven, d=50mm (2")                                                    |
| 922743                                | Holder for trolley handle (when trolley is in the oven) for 201 and 202 combi ovens                        |
| 922778                                | Kit for installation of electric power peak management system for 20 GN Oven                               |
| <b>Kit Compatibility Air-O-System</b> |                                                                                                            |
| 922770                                | KIT COMPATIBILITY FOR AOS/EASYLINE TROLLEYS (PRODUCED TILL 2019) WITH SKYLINE/MAGISTAR COMBI OVENS 20GN2/I |
| 922771                                | KIT COMPATIBILITY FOR AOS/EASYLINE OVENS 20GN WITH SKYLINE/MAGISTAR TROLLEYS                               |
| <b>Other Accessories</b>              |                                                                                                            |
| 922338                                | Smoker for ovens                                                                                           |
| <b>Spray Units</b>                    |                                                                                                            |
| 922171                                | External side spray unit                                                                                   |
| <b>Ventilation</b>                    |                                                                                                            |
| 922776                                | Extension for condensation tube, 37cm                                                                      |
| <b>Wall Mounting Kits</b>             |                                                                                                            |
| 922687                                | Kit to fix oven to the wall                                                                                |
| <b>Water Treatment</b>                |                                                                                                            |
| 864388                                | External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens               |
| 920003                                | Water softener with cartridge STEAM 1200                                                                   |
| 920005                                | Water filter with cartridge and flow meter for medium steam usage                                          |
| <b>Other Accessories</b>              |                                                                                                            |
| 922773                                | WATER INLET PRESSURE REDUCER                                                                               |

## Recommended Detergents

| PNC Code | Description                                        |
|----------|----------------------------------------------------|
| 0S2394   | C25 Rinse & Descale Tabs, 50 tabs bucket           |
| 0S2395   | C22 Cleaning Tabs, phosphate-free, 100 bags bucket |



Find out more:  
ISO Certificates  
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/09/11

7/7