

EUERES

BACK BAR COOLER

Project Name: _

Model #:__

Project Location:

___ Quantity: ____

Available Warehouse:_

Model: EBB48 **EBB Series**



Refrigeration System

Side mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.

- Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- Full-length air duct system ensures optimal circulation of cold air.
- · Time-initiated and temperature-terminated auto defrost cycle for seamless operation.
- · Large capacity, corrosion-resistant condenser and evaporator coils.

Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.
High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning. Refer to owner's manual for full maintenance instructions.
Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

Cabinet Construction

- Heavy duty stainless steel countertop with textured laminate, black vinyl exterior.
 Open spaced interior with no walls between compartments.
 Galvanized steel interior walls and high quality stainless steel floor.

- · 1 3/4" thick high density polyurethane insulation.
- Built-in caster thread receptacles for all models.

Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

Doors

- · Textured laminate, black vinyl exterior with galvanized steel interior.
- 1 3/4" thick high density polyurethane insulation.
- Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, recessed door handles.
- Pre-installed door locks keep your items safe from theft.

Shelving

- · Two epoxy coated, steel wire shelves per section.
- · Height adjustable stainless steel clips.

Temperature Control

- Multi-function digital controller with easy to read LED display.
 Factory preset temperature, 35°F. Temperature setting range from 33°F to 54°F.
- · Audible overheat protection alarm for compressor and condenser coil.

Options

- · Additional shelving.
- \cdot 3" or 5" swivel casters with locks. \cdot 3.5" 6" height-adjustable and interchangeable legs.





Please visit our website for updated Energy Efficiency information

Ref/ Frz/Dual	Doors	Capacity		Shelves Refrigerant	Refrigerant	НР	Power	Amps	Crated	Exterior Dimensions			
		Cu. Ft.	12 oz. Cans	12 oz. Bottle		nonigorant		V-Hz-Ph	Ampo	Weight	L	D	H*
REF	2	14	490	344	4	R-290	1/4+	115-60-1	3.5	269 lbs (122kg)	49" (1245mm)	27" (686mm)	37.25" (946mm)

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (★) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.



BACK BAR COOLER

EBB Series

Model: EBB48

DIMENSIONAL D	ATA			
	L	49" (1245mm)		
External Dimensions	D	27" (686mm)		
	H*	37.25" (946mm)		
Crated Weight		269 lbs. (122kg)		
Doors/Drawers/Lids		2		
Max Weight Support (-			
STORAGE DATA				
Net Capacity Cu. Ft. 🏲	Net Capacity Cu. Ft. 🏲			
Shelves		4		
Barrels	-			
20 oz. Bottles		-		
12 oz. Bottles	12 oz. Bottles			
12 oz. Cans	12 oz. Cans			
8" Mugs	8" Mugs			
# of Pans (Top)	-			
# of Pans (Drawer)	-			
Dividers		-		
Trays		-		
ELECTRICAL DAT	A			

115-60-1

(I) NEMA 5-15P

3.5A

3

9ft

Side


R-290

1/4+

1926

49" EVEREST 37 1/4" 18 1/2" 18 1/2"

PLAN VIEW



FRONT

34 1/4" 27" 44 3/4" TOP

Air Flow

SIDE

AIRFLOW

ACCESSORIES & OPTIONS

Part Number	Description
Additional Shelving	Contact Everest Refrigeration for more information.
AJL03-00	Interchangeable Leg for Caster
CASA3-01	3" Overall Height Caster Assembly - (2) Front (2) Rear
CASA5-01	5" Overall Height Caster Assembly - (2) Front (2) Rear

F. (310) 323-7524

KEY

Voltage

Cord Length

Refrigerant

BTU/HR[†]

Compressor HP

NEMA Plug Type

Full Load Amperage

Feed Wires with Ground

REFRIGERATION DATA Compressor Mounting

D	Door	R	Refrigerator	
L	Lid	REF	Refrigerator	
H	Half Door	F	Freezer	
FD	Full Door	FRZ	Freezer	
SD	Solid Door	DUAL	REF/FRZ Combo	
GD	Glass Door	DR	Drawer	

	Elevation	Right	Plan	3D	Back
KCL					

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (★) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.

VER. 8/6/2019