	Project Name: _		AIA#:
Model #: _	•	Location:	



Globe 60 Quart Planetary Pizza Floor Mixer

Robust size and power for handling pizza dough!

Features two fixed speeds and operatorfriendly power bowl lift.









Model

☐ SP62P — Pizza Mixer

Standard Features

- Powerful 3 HP custom built motor
- Gear-driven, high-torque transmission
- Heat-treated hardened steel alloy gears & shafts
- Two fixed speeds
- Handles up to 50 lbs. of flour (80 lb. batch size)
- Permanently lubricated oil bath transmission
- Thermal overload protection
- Front-mounted touch pad controls with 60-minute digital timer and last-batch recall
- Stainless steel, interlocking bowl guard with built-in, fully welded ingredient chute
- Safety interlocked power bowl lift
- Heavy duty bowl truck (pictured)
- Rigid cast iron body
- Industry standard #12 attachment hub
- NSF approved enamel gray paint
- 6-foot cord and ground plug
- Auto shut off, for operator safety plus motor and transmission protection

Standard Accessories/Attachments

- 60 qt. stainless steel bowl (#304 series)
- Aluminum spiral dough hook
- Non-slip rubber feet
- Bowl truck

Warrantv


Two years parts and labor

Optional Attachments/Accessories


- Seismic flange kit
- Slicer/shredder/grater for #12 hub
- Meat grinder for #12 hub
- Meat tenderizer for #12 hub
- Strip cutter for #12 hub
- Aluminum flat beater
- Stainless steel wire whip
- Additional bowl truck
- Correctional package
- Extended warranty

To select options see back

Approved by:	Date:



30.25 (76.8)



Drawings available through KCL at www.kclcad.com.

SPECIFICATIONS											
Model	Motor	Volts	Amps	Transmission Type	Capacity	Controls	Power Bowl Lift	Agitator Sp First	Second	Attachment First	Speeds (RPMs) Second
SP62P (1 Phase)	3 HP	220/60/1	18	Gear	60 qt / 57 liter	Digital, front mounted	1/8 HP Motor	56	98	64	110
SP62P (3 Phase)	3 HP	208/60/3	12	Gear	60 qt / 57 liter	timer and controls					

Cord & Plug: Attached 6-foot flexible 3-wire cord with molded plug fits a grounded receptacle. Single phase NEMA L6-30P (1) Three phase NEMA L15-20P (1) *Specify voltage when ordering.

DIMENSIONS | SHIPPING INFORMATION

Reinforced carton for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to shipment. This product ships on a pallet. Freight class 85.

Model	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight
SP62P	30.25" W x 41.6" D x 60" H (76.83 cm x 105.66 cm x 152.4 cm)	980 lbs (444 kg)	48" W x 48" D x 76" H (122 cm x 122 cm x 193 cm)	1,228 lbs (556 kg)

Mixer is constructed of a rigid cast iron body with front-mounted controls and 60-minute digital timer. Mixer has 3 HP custom built motor with overload protection and gear-driven, high torque permanently lubricated 2 speed transmission consisting of heat-treated hardened steel alloy gears and shafts. Mixer comes standard 60 qt. stainless steel bowl, stainless steel bowl truck, aluminum dough hook and non-slip rubber feet. Interlocked with stainless steel bowl guard with fully welded ingredient chute. Mixer has #12 attachment hub and interlocked bowl lift. Mixer is NSF and ETL listed. Two-year parts and labor warranty.

OPTIONAL MIXER ACCESSORIES AND HUB ATTACHMENTS

- ☐ XXSEISMIC KIT-LG Seismic kit ☐ XXBOWL-62 60 qt. stainless steel
- (S/S) bowl ☐ XXBEAT-62 Alum. flat beater
- ☐ XXHOOK-62 Alum. dough hook ☐ XXWHIP-62 S/S wire whip
- ☐ XBTRUCK-62 Heavy-duty bowl truck

- XVSGH 9" Slicer/Shredder/Grater housing only (no plates included-must select from plates listed on this sheet)
- ☐ XASP Adjustable slicing plate (for vegetables only)
- ☐ XPH Plate holder

- **L00670** Meat Tenderizer attachment ☐ L00783 Strip Cutter attachment
- Shredding Plates:
- ☐ XSP332* 3/32" (2.3 mm) **☐ XSP316*** 3/16" (4.7 mm)
- XSP14* 1/4" (6.3 mm) **☐ XSP516*** 5/16" (7.9 mm)
- ☐ XSP12* 1/2" (12.7 mm)☐ XGP* Grating plate
- *Only 1 plate holder required ☐ XMCA-SS Meat grinder assembly
 - (Polished stainless steel cylinder, worm gear, ring, and s/s pan. Includes knife, 3/16" plate, and pusher.)

- ☐ XXCK Chopper knife for XMCA-SS
- Chopper Plate Sizes Available: ☐ CP02-12 1/16" (2 mm) ☐ **CP04-12** 5/32" (4 mm) **□ CP05-12** 3/16" (5 mm)
- ☐ CP06-12 1/4" (6 mm) ☐ CP08-12 5/16" (8 mm) ☐ CP10-12 3/8" (10 mm)
- ☐ CP12-12 1/2" (12 mm) ☐ **CP14-12** 9/16" (14 mm) ☐ CP16-12 5/8" (16 mm)
- ☐ CP18-12 11/16" (18 mm) ☐ CP00-12 Stuffing plate ☐ XST12 1/2" Stuffing tube (mutton)

- ☐ XST34 3/4" Stuffing tube (pork)
- ☐ FACTORY INSTALLED OPTION: XXCORR-62 Correctional package, includes tamper resistant external fasteners.
- ☐ EXTENDED WARRANTY SP-XDSPL Extended warranty for SP62P mixer, extends factory warranty to 3 years. Available only at time of purchase.

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 |

www.globefoodequip.com