



ELECTRIC
PROVECTION OVEN

IMPERIAL



PRVE-1

Model Numbers

PRVE-1
PRVE-2
PRVE-3

OVEN FEATURES

- All stainless steel exterior.
- 1/2 HP, 2 speed motor.
- Cool down feature.
- Two low watt density elements for long life.
- 7.5 KW output.
- Removable rack guide assembly.
- Five rack positions.
- Three oven racks included.
- Stainless steel oven door handle.
- Doors with tempered glass windows.
- Two HID oven interior lights with momentary switch.
- Full porcelain interior.
- Stackable up to three units high.
- Can be used as a base for countertop units or built-in as part of Spec and Pro Series ranges.
- Available in 208, 240 and 480 volts.
- Tested to UL197 threshold of 5mg/m3.



ELECTRICAL REQUIREMENTS PER OVEN				
TOTAL KW	VOLTS	PH	HERTZ	AMPS
7.5	208	1	50/60	40
7.5	208	3	50/60	25
7.5	240	1	50/60	35
7.5	240	3	50/60	22
7.5	480	3	50/60	13

CLEARANCE REQUIREMENTS

Legs or stand required for non-combustible surfaces.
Provide 0" clearance from non-combustible surfaces
and 8" (203 mm) from combustible surfaces.

