

Modular Ice Maker KCM-1100-AH



Durable Design

- Created to endure the every day use of your commercial environment
- Simple plug-in installation
- High quality construction to ensure reliability, longevity and product durability

Energy Efficiency

 Improved evaporator freezing surface allowing for increased production and lower operating costs

Half Cube Dimensions



A: 1.10" B: 0.30" C: 0.80"

Superior Quality

- Designed for efficiency and dependability
- Stainless steel exterior for superior resilience to rust
- Simple to use
- Control board with on-board self-diagnostics
- Internal safety switches monitor and protect the refrigeration system
- Easy maintenance removable bin cover allows for easy access to the inner components
- Up to 1106 lbs of ice production per 24 hrs



Bin KB-440 shown above is not included - sold separately

Project Name:	
Location:	
Item:	Qty:
Model:	















5659 Royalmount Ave.
Montreal, QC, Canada H4P 2P9
Telephone: 514.737.9701 / Toll Free: 888.275.4538
Fax: 514.342.3854 / Toll Free: 877.453.8832
sales@mvpgroupcorp.com / mvpgroupcorp.com

12000 Biscayne Blvd., Suite # 108 Miami, FL, United States 33181 Telephone: 786.600.4687 / Toll Free: 844.218.8477 Fax: 786.661.4100







- A: Water Inlet (3/8" FPT) B: Drain (3/4" FPT)
- C: Power Cord

Dimensions with KB-350 Bin * unit sold separately

Height: 72.10" (includes 4" feet)

Width: 30" Depth: 34.30"

Bin storage: 354 lbs / 160 kgs

Dimensions with KB-440 Bin * unit sold separately

Height: 80" (includes 4" feet)

Width: 30" Depth: 34.30"

Bin storage: 442 lbs / 200 kgs

24 Hour Volume Production

Air	Water	Production
70°F / 21°C	50°F / 10°C	1106 lbs
90°F / 32°C	70°F / 21°C	772 lbs



Operating Requirements

	Min	Max
Air Temperatures	50°F / 10°C	100°F / 38°C
Water Temperatures	41°F / 5°C	90°F / 32°C
Water Pressure	14 PSI	80 PSI
Electrical Voltage 115 / 60 / 1	- 8%	+ 10%



Specifications

Model Number	Electrical V / Hz / Ph	BTU's per Hour	Max Fuse Size or HACR Circuit Breaker Amps	Net Weight lb / kgs	Shipping Weight lb / kgs	Refrigerant
KCM-1100-AH	208-230 / 60 / 1*	18500	15 A	256 / 116	291 / 132	R-404a

*Unit comes without a cord set or plug. Unit to be connected per local electrical codes.

Energy Consumption kWh / 100 lb 90°F (32°C) / 70°F (21°C)	Water Usage / 100 lb of ice @ 90°F air / 70°F water	Plumbing
5.11 kWh	20 gallons / 76 litres	Water Inlet: 3/8" Drain: 3/4"

Ice Maker Dimensions (not including bin) (W x D x H in inches)

Cabinet: 30" x 25" x 30"

Shipping: 34" x 28.50" x 36.75"

Clearance around the unit: left, right, top and rear: 8"

Do not place near ovens, grills or any high heat producing equipment

Warranty: 3 years parts and labor

Compressor: 5 years parts and 3 years labor

Valid in United States, Canada & Puerto Rico. Please contact factory for warranty in other countries.

 ${f Kool-it}$ is a registered trademark of MVP Group.

Specifications and design are subject to change without prior notice



5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Telephone: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com Replace the filters every 6 months with part #KTI-2













12000 Biscayne Blvd., Suite # 108 Miami, FL, United States 33181 Telephone: 786.600.4687 / Toll Free: 844.218.8477 Fax: 786.661.4100