



Refrigerators Undercounter KUCR Series

KUCR-27-1 | KUCR-36-2
KUCR-48-2 | KUCR-60-2 | KUCR-72-3

Durable Design

- Created to endure the everyday stress of the commercial kitchen environment, to protect your long term investment and guarantee superior food preservation
- Coated evaporator coil
- 2 height adjustable, heavy-duty, PE coated wire shelves per door
- Spring loaded, self-closing doors
- Door swing is field reversible on 27" units (part KB-5246 required)

Energy Efficient

- Self-closing door with stay open feature
- Self-closing door with 45° stay-open feature
- Improved magnetic door seal gasket
- Foamed-in place high-density polyurethane insulated body, CFC-Free

Superior Quality

- Designed for mobility, reliability & efficiency in commercial kitchens
- 4" swivel casters with 2 front brakes (2.5" casters can be ordered as option)
- 36" high working surface
- Easy grip door handle(s)
- Entirely self-contained system
- Forced air refrigeration
- Automatic defrost system
- Easily adjustable shelf height
- Stainless steel interior & exterior
- KUCR Series Undercounter Refrigerators Temperature range : 33°F to 40°F



Intertek Intertek

Nema 5-15P
Dedicated Circuit

Project Name:	
Location:	
Item:	Qty:
Model:	



5659 Royalmount Ave.
Montreal, QC, Canada H4P 2P9
Telephone: 514.737.9701 / Toll Free: 888.275.4538
Fax: 514.342.3854 / Toll Free: 877.453.8832
sales@mvpgroupcorp.com / mvpgroupcorp.com

12000 Biscayne Blvd., Suite # 108
Miami, FL, United States 33181
Telephone: 786.600.4687 / Toll Free: 844.218.8477
Fax: 786.661.4100



Refrigerators Undercounter KUCR Series

KUCR-27-1 | KUCR-36-2
KUCR-48-2 | KUCR-60-2 | KUCR-72-3



KUCR-27-1



KUCR-36-2




KUCR-48-2



KUCR-60-2



KUCR-72-3



Model Number	Capacity (cubic feet)	Number of Doors	Number of Shelves	HP	Amps	Refrigerant	Net Weight (lbs.)	Shipping Weight (lbs.)	Shipping Dimensions (W x D x H inches)	External Dimensions (W x D x H inches)	Internal Dimensions (W x D x H inches)
KUCR-27-1	7	1	2	1/4	3.6	R290	143	169	28.9 x 34.1 x 36.6	27.5 x 30 x 35.9	24.7 x 27.2 x 28.9
KUCR-36-2	9.5	2	4	1/4	3.8	R290	172	189	37.8 x 34.1 x 36.6	36.4 x 30 x 35.9	33.4 x 27.2 x 28.9
KUCR-48-2	13.1	2	4	1/4	3.9	R290	194	247	49.7 x 34.1 x 36.6	48.4 x 30 x 35.9	43.3 x 20.1 x 26.5
KUCR-60-2	16.7	2	4	1/4	4.7	R290	236	287	61.8 x 34.1 x 36.6	60.4 x 30 x 35.9	55.4 x 20.1 x 26.5
KUCR-72-3	20.2	3	6	1/4	5.2	R290	263	294	73.8 x 34.1 x 36.6	72.4 x 30 x 35.9	67.5 x 20.1 x 26.5



Nema 5-15P
Dedicated Circuit

These units are designed for maximum performance in an air-conditioned area of 75°F ambient temperature and 55% relative humidity. There must be adequate ventilation at the top, sides & rear of the unit for proper operation.

Warranty: 36 months parts and labor.
Additional 24 months on compressor (part only)

KOOL-IT is a registered trademark of MVP Group.
Specifications subject to change without notice.



5659 Royalmount Ave.
Montreal, QC, Canada H4P 2P9
Telephone: 514.737.9701 / Toll Free: 888.275.4538
Fax: 514.342.3854 / Toll Free: 877.453.8832
sales@mvpgroupcorp.com / mvpgroupcorp.com

12000 Biscayne Blvd., Suite # 108
Miami, FL, United States 33181
Telephone: 786.600.4687 / Toll Free: 844.218.8477
Fax: 786.661.4100