



For questions or ordering info:

Phone: (917) 525-2066

Email: support@kitchenall.com

Web: www.kitchenall.com

Kitchenall
New York Restaurant Equipment

Refrigerated Salad Bar / Buffet Table

Don't see the size that you're looking for? We can customize it!



PRODUCT HIGHLIGHTS

- Lecumseh Compressor
- 5" Casters Standard
- Durable and Easy to Adjust
- Holds 36°F ~ 41°F
- Defrost Timer System
- ETL UL Certified
- Aluminum Sides and Top with Stainless Steel Floor
- High-Density Polyurethane Foam Insulation (CFC Free)
- Self closing door
- Adjustable Epoxy Wire Shelves
- Sneeze Guard Optional
- Single or Double Service Configuration



MODEL	WXDXH	DOORS	SHELF	VOLTS	H.P.	FITS 1/3 PAN	WEIGHT
BT36	36X32X36	1 1/2	1	115	1/4	6	176
BT36-DS	36X34X36	1 1/2	1	115	1/4	6	176
BT48	48X32X36	1 1/2	1	115	1/3	9	208
BT48-DS	48X34X36	1 1/2	1	115	1/3	9	208
BT60	60X32X36	1 1/2	1	115	1/3	12	228
BT60-DS	60X34X36	1 1/2	1	115	1/3	12	228
BT72	72X32X36	2 1/2	3	115	1/3	15	285
BT72-DS	72X34X36	2 1/2	3	115	1/3	15	285
BT84	84X32X36	2 1/2	3	115	1/3	18	350
BT84-DS	84X34X36	2 1/2	3	115	1/3	18	350
BT96	96X32X36	3 1/2	3	115	1/2	21	400
BT96-DS	96X34X36	3 1/2	3	115	1/2	21	400
BT118	118X32X36	4	4	115	3/4	27	345
BT118-DS	118X34X36	4	4	115	3/4	27	345

Additional Features:

- Units comes with Single Service as a standard configuration. (2" Extension Front Only)
- Option to upgrade to Double Service configuration. (2" Extension Front / Back)
- Option to add to Sneeze Guard Canopy. (Does not come attached to the unit and must be assembled)
- Our defrost timer system keeps cooling systems separate from the evaporator. It doesn't ice up or inhibit the compressor, giving the unit outstanding performance and a longer life even in the most difficult environments.
- These models are designed to operate in an environment where temperature and humidity do not exceed 75°F and 65% relative humidity.