



For questions or ordering info:
 Phone: (917) 525-2066
 Email: support@kitchenall.com
 Web: www.kitchenall.com

Kitchenall
 New Restaurant Equipment

Solid Door Cooler

Don't see the size that you're looking for? We can customize it!



PRODUCT HIGHLIGHTS

- Tecumseh Compressor
- Defrost Timer System
- Stainless Steel front, top and sides
- High-Density polyurethane foamcell insulation (CFC Free)
- Self closing door
- Adjustable epoxy wire shelves
- Mechanically Controlled Uniform Temperature
- Defrost Timer System
- Front Breathing
- Solid Stainless Steel Grille
- Holds 36°F ~41°F
- ETL UL Certified



MODEL	WXDXH	DOORS	SHELF	VOLTS	H.P.	CU.FT	WEIGHT
LR30 S/C	30X32X75	1	3	115	1/3	20	300
LR30 R	30X32X75	1	4	115	-	26	250
LR48 S/C	48X32X75	2	3X2	115	1/3	34	375
LR48 R	48X32X75	2	4X2	115	-	44	325
LR54 S/C	54X32X75	2	3X2	115	1/3	38	420
LR54 R	54X32X75	2	4X2	115	-	50	350
LR79 S/C	79X32X75	3	3X3	115	1/2	59	600
LR79 R	79X32X75	3	4X3	115	-	75	530
LR104 R	104X32X75	4	4X3	115	-	101	800
LR129 R	129X32X75	5	4X3	115	-	126	980

Additional Features:

- Self evaporated water from evaporator (for self-contain models only)
- Our defrost timer system keeps cooling systems separate from the evaporator. It doesn't ice up or inhibit the compressor, giving the unit outstanding performance and a longer life even in the most difficult environments.
- These models are designed to operate in an environment where temperature and humidity do not exceed 75°F and 65% relative humidity.

*Remote unit price doesn't include any cooling system assembly parts (Evaporator only)