



For questions or ordering info:
 Phone: (917) 525-2066
 Email: support@kitchenall.com
 Web: www.kitchenall.com

Kitchenall
 New Restaurant Equipment

Sliding Glass Door Soda Case

Don't see the size that you're looking for? We can customize it!



PRODUCT HIGHLIGHTS

- Tecumseh Compressor
- Defrost Timer System
- Stainless Steel front, top and sides
- High-Density polyurethane foamcell insulation (CFC Free)
- Self closing door
- Adjustable epoxy wire shelves
- Mechanically Controlled Uniform Temperature
- Defrost Timer System
- Front Breathing
- Solid Stainless Steel Grille
- Holds 36°F ~41°F
- ETL UL Certified



MODEL	WXDXH	DOORS	SHELF	VOLTS	H.P.	CU.FT.	WEIGHT
LS38 S/C	38X30X75	2	2X3	115	1/3	26	325
LS38 R	38X30X75	4	2X4	115	-	33	300
LS48 S/C	48X30X75	2	2X3	115	1/3	34	385
LS48 R	48X30X75	4	2X4	115	-	43	355
LS54 S/C	54X30X75	2	2X3	115	1/3	38	430
LS54 R	54X30X75	4	2X4	115	-	49	400
LS72 S/C	72X30X75	2	2X3	115	1/2	53	610
LS72 R	72X30X75	4	4X4	115	-	66	560
LS79 S/C	79X30X75	3	3X3	115	1/2	57	680
LS79 R	79X30X75	6	3X4	115	-	68	600
LS96 S/C	96X30X75	4	4X3	115	3/4	71	780
LS96 R	96X30X75	8	4X4	115	-	89	700
LS120 S/C	120X30X75	4	4X3	115	3/4	82	980
LS120 R	120X30X75	8	4X4	115	-	114	900

Additional Features:

- Self evaporated water from evaporator (for self-contain models only)
- Our defrost timer system keeps cooling systems separate from the evaporator. It doesn't ice up or inhibit the compressor, giving the unit outstanding performance and a longer life even in the most difficult environments.
- These models are designed to operate in an environment where temperature and humidity do not exceed 75°F and 65% relative humidity.

*Remote unit price doesn't include any cooling system assembly parts (Evaporator only)