



For questions or ordering info:  
 Phone: (917) 525-2066  
 Email: support@kitchenall.com  
 Web: www.kitchenall.com

**Kitchenall**  
 New Restaurant Equipment

# Worktop Cooler

Don't see the size that you're looking for? We can customize it!



## PRODUCT HIGHLIGHTS

- Tecumseh compressor
- Defrost Timer System
- Exterior - Stainless Steel front, top and sides
- Interior - Aluminum sides and top with stainless steel floor
- High-Density Polyurethane foam cell insulation (CFC Free)
- Self Closing Door
- Adjustable epoxy wire shelves
- Standard 5" Casters
- Holds 36°F ~40°F
- ETL UL Certified



MODEL	WXDXH	DOORS	SHELF	VOLTS	H.P.	CU.FT.	WEIGHT
LB27 S/C	27X32X36	1	1	115	1/4	7.8	142
LB27 R	27X32X36	1	1	115	-	9.7	114
LB36 S/C	36X32X36	1 1/2	1	115	1/4	11.2	188
LB36 R	36X32X36	2	2	115	-	13.5	143
LB48 S/C	48X32X36	1 1/2	1	115	1/4	14.7	198
LB48 R	48X32X36	2	2	115	-	18.5	162
LB60 S/C	60X32X36	1 1/2	1	115	1/4	19.6	230
LB60 R	60X32X36	2	2	115	-	23.6	195
LB72 S/C	72X32X36	2 1/2	2	115	1/3	24.8	330
LB72 R	72X32X36	3	3	115	-	28.6	260
LB84 S/C	84X32X36	2 1/2	2	115	1/3	29.9	380
LB84 R	84X32X36	3	3	115	-	33.7	340
LB96 S/C	96X32X36	3 1/2	3	115	1/2	35.0	410
LB96 R	96X32X36	4	4	115	-	38.8	324
LB118 S/C	118X32X36	4 1/2	4	115	3/4	44.4	460
LB118 R	118X32X36	5	5	115	-	48.0	400

### Additional Features:

- Our defrost timer system keeps cooling systems separate from the evaporator. It doesn't ice up or inhibit the compressor, giving the unit outstanding performance and a longer life even in the most difficult environments.
- These models are designed to operate in an environment where temperature and humidity do not exceed 75°F and 65% relative humidity.