

PD Series, Remote & Self-Contained, Open Produce Merchandisers



Features

- Decorator colored sides of your choice from Marc's enormous inventory
- Night Shades lock in your refrigeration overnight
- Full length mirror to enhance product visibility
- Freon valve installed on remote and self contained models
- Dial thermometer for accurate temperature readings
- Dry storage bins maximizing total storage capacity
- Enhanced product lighting from top canopy and under lower level of wire baskets with safety sleeves
- Two levels of wire baskets in long lasting white epoxy
- Product dividers for wire baskets and main deck
- > Drain is 1" pipe thread for easy cleaning (drain connection required in field, remote and self-contained models)
- ▶ Front bumper made of high density PVC for shopping cart impact
- ▶ Side panels have 1/4" plexiglass for maximum visibility and safety.
- Insulation is full density, solid core urethane
- Automatic time clocks are standard for self-contained models
- Mirror finish stainless steel trim, caps, moulding and main deck

Marc's PD Series Open Produce Merchandisers

MODEL	LENGTH	HEIGHT	DEPTH	Unit Installed	Unit recommended (not included)	Storage Bins	Electrical Data	Product Dividers		Approx. Shipping Weight
								Baskets	Main Deck	
PD-6R	72 1/2 "	78 1/2"	34 1/2 "	х	1 H.P*	4	115/1/60	12	5	700 lbs.
							4.0 amps			
PD-8R	94 1/2 "	78 1/2"	34 1/2 "	х	2 H.P*	6	115/1/60	18	7	800 lbs.
							6.4 amps			
PD-10R	116 1/2 "	78 1/2"	34 1/2 "	x	3 H.P*	6	115/1/60	18	9	1000 lbs.
							6.7 amps			
PD-12R	138 1/2 "	78 1/2"	34 1/2 "	х	3 H.P*	8	115/1/60	24	11	1140 lbs.
							8.6 amps			
PD-6S/C	72 1/2 "	78 1/2"	34 1/2 " plus 3" removeable wall spacer for compressor	1 H.P	x	2	115/1/60 6.4 amps		5	775 lbs.
							units & fans	12		
							230/208-60-1 10.5 amps			
			air flow				units & clock			
PD-8S/C	94 1/2 "	78 1/2"	34 1/2 " plus 3"	us 3" 1 H.P oveable spacer or	х	4	115/1/60 6.4 amps		_	930lbs.
			removeable				units & fans	18	7	
			for				230/208-60-1			
			compressor air flow				10.5 amps units & clock			

NOTE: Designed for use in locations with air conditioning where temperature and relative humidity do not exceed 75% F and 55% RH.

* This size condenser unit is RECOMMENDED for this model. Consult a competent refrigeration mechanic to determine the appropriate size for your specific application. The appropriate condenser will vary depending on length of run, indoor/outdoor use, etc.



