



NOVA22PDC



45.5" x 30" x 27.25" (H x W x D)

30" wide fully assembled commercial dipping cabinet made in Europe with digital thermostat, sneezeguard, and light

Highlights:

Fully assembled dipping cabinet with durable polycarbonate sneezeguard and light

Digital thermostat for easy temperature control, with a wide range between -13 and 23°F to accommodate ice cream, gelato, and other frozen treats

Tub holder baskets for convenient ice cream storage

Product Features:

Commercially approved	UL-S listed to NSF-7 Standards for use in commercial establishments
Sneezeguard	Durable polycarbonate sneezeguard with light is pre-installed
Digital thermostat	Electronic controls for more precise temperature management
Wide temperature range	Digital thermostat can be set between -13 and +23°F to accommodate a variety of frozen treats
Ice cream tub holders	Two epoxy coated wire baskets with plastic lids included to hold standard ice cream tubs in place
Holds 6 standard 3 gallon tubs	Unit can store 2 tubs on the floor and display an additional 4 using the provided baskets
Sliding glass lid	Two tempered glass lids glide smoothly for easy use
Strong insulation	3" thick insulation helps to ensure items stay cold
Manual defrost	Static cooling system for improved temperature stability

NOVA22PDC Specifications:

Overview	
Height of Cabinet	45.5" (116 cm)
Width	30.0" (76 cm)
Depth	27.25" (69 cm)
Capacity	7.2 cu.ft. (204 L)
Defrost Type	Manual
Door	Glass
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	7.2
Voltage/Frequency	115 V AC/60 Hz
Weight	130.0 lbs. (59 kg)
Shipping Weight	140.0 lbs. (64 kg)
Estimated Time to Ship	5 to 7 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	Sliding
Interior Height	26.0" (66 cm)
Interior Width	23.75" (60 cm)
Interior Depth	21.0" (53 cm)
Thermostat Type	Digital
Refrigerant Type	R290a
Refrigerant Amount	3.03 oz.
High Side PSI	345.0
Low Side PSI	140.0
Compressor Step Height	9.75" (25 cm)
Compressor Step Width	7.88" (20 cm)
Compressor Step Depth	21.0" (53 cm)
Temperature Range	-13 to 23°F

