		Model:	Project Name	LOCATION		
			Ітем #	QTY	AIA #	
REFRIGERATION DIVISION		TBR60-PTSZ1-L-S-GG-GG-1	Model #		SIS #	
JE MANUFACTURING CO., INC. East Terra Lane ● O'Fallon, Missouri 63366-4434 ● (636)272-2408 ● Toll Free (800)325-6152 ● Intl Fax# s Dept. (800)424-TRUE ● Parts Dept. Fax# (636)272	(001)636-272-7546	<b>True Bar Refrigerator:</b> Pass-Thru Single Zone Refrigerator				
				FEA	TURES	
	)			R290 Hydrocar	bon refrigerant	
				Temperatures of to 3.3°C)	of 33°F to 38°F (.5°C	
				Exterior: Stainle	ess steel	
				Interior: Stainle	ess steel	
itana.				RCU Technolog	RCU Technology	
	Alternation			White LED inte	rior lighting	
				NSF/ANSI stand open food prod	dard 7 compliant fo duct	
				UL Rated for out	utdoor use	
				Three (3) interi	or access ports	
				Field reversible	doors	
				Zero clearance	(side and back)	
				Front air intake	/ front air discharg	
				Electronic tem exterior digital	perature control w display	

# **ROUGH-IN DATA**

Specifications subject to change without notice. Chart dimensions rounded up to the nearest ½" (millimeters rounded up to next whole number).

			Сара	acity 12 oz.	Cabinet Dimensions (inches) (mm)		115V/60/1 Voltage			Cord Length‡ (total ft.)	Crated Weight	
Model	Doors Shelv	Shelves	helves 12 oz. Cans	Bottles	W	D†	Н	HP	Amps	NEMA	(total m)	(lbs.) (kg)
TBR60-PTSZ1-L-S-GG-GG-1	4	6	89 6-pks	57 6-pks	60 1524	27 684	34¾ 881	1⁄4	3.2	5-15P	10 3.04	TBD TBD

† Depth does not include 1½" (35 mm) for door handles. \* Height does not include ¼" (7 mm) for leg levelers ‡ Cord length listed represents usable cord length.

IN THE USA	APPROVALS:	AVAILABLE AT:
5/20 - MS		

### Model:

# TBR60-PTSZ1-L-S-GG-GG-1

## ADDITIONAL FEATURES

#### **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system
- Environmentally friendly R290 hydrocarbon refrigerant
- Forced air refrigeration system which maintains 33°F to 38°F (.5°C to 3.3°C) product temperatures
- Exclusive RCU technology allows for the reversing of the condensor fan motor, helping to keep the condensing coil clean and reduce the negative effects of a dirty coil

#### **CABINET CONSTRUCTION**

- Exterior: Stainless steel front, sides, and countertop
- Interior: Stainless steel floor and sides with ABS plastic ceiling
- Insulation: Entire cabinet is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion and zero global warming potential
- Base fitted with leg levelers

PLAN VIEW

# True Bar Refrigerator: Pass-Thru Single Zone Refrigerator

#### DOORS

- Low-E, double pane thermal insulated glass doors with black powder coated door frames
- Door locks standard
- Field Reversible Doors standard (reverse hinge kit included)

#### SHELVING

- Six (6) adjustable, gray PVC coated wire shelves. 21 <sup>11</sup>/<sub>6</sub> <sup>11</sup>W x 18"D (551 mm x 458 mm). Four (4) chrome plated shelf clips included per shelf.
- Aluminum shelf support pilasters. Shelves are adjustable on  $\, \ensuremath{\sc 2}$  "(13 mm) increments.

#### **MODEL FEATURES**

- NSF/ANSI Standard 7 compliant for open food
- UL approved for outdoor use
- Electronic temp control with exterior digital display
- Three (3) access ports standard (see drawing for locations)

• Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.


T | | P

REFRIGERATION





#### **OPTIONAL FEATURES/ACCESSORIES** Upcharge and lead times may apply.

- TruLumina® 14-Color LED lighting
- Castors: <sup>7</sup>/<sub>8</sub> " (23 mm) rollers, 2" (51mm), 3" (77mm), 4" (102mm), 5" (127mm) castors
- G" (153mm) legs
- G" (153mm) seismic legs
- □ Alternative temperature zones available (contact factory)
- Right side compressor









## TOP VIEW

### **PLAN VIEW NOTES**

- Dimensions in brackets are in millimeters.
- Depth does not include 1 1/2 " (35 mm) for door handles.
- Height does not include 1/4 " (7 mm) for leg levelers
- Front of cabinet is side with control/display.



BACK VIEW

SIDE VIEW

26 9/16"

[675]

[762]

[684] 0

784

Ø 1" [25] ACCESS OPPOSITE

CONDENSING UNIT 3 15/16" [100] 4 5/16"

[110]

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

### TRUE MANUFACTURING CO., INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com

## ELECTRICAL