Τπιε	me:	A		
		Location:		
	'Fallon, Missouri 63366-4434 • (636)240-2400 ee (800)325-6152 • Intl Fax# (001)636-272-7546	Item #:	<i>Qty:</i>	S
Parts Dept. (800)424-TRUE • P	arts Dept. Fax# (636)272-9471 • www.truemfg.com	Model #: _		
Model: FLM-81F~TSL01	Full Length Merchandiser: Swing Door Freezer with Hydrocarbo	on Refrigera	nt~True Standard Look Versior	n 01
	· · · · · · · · · · · · · · · · · · ·			





FLM-81F~TSL01

AIA #

SIS #

- The world's #1 manufacturer of glass door merchandisers.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains -10°F (-23.3°C) temperatures. Ideal for both frozen foods and ice cream.
- Exterior non-peel or chip black powder coated cold rolled steel ends with black aluminum cabinet top and back; durable and permanent.
- Interior attractive, white aluminum interior liner with stainless steel floor.
- Double pane thermal insulated glass swing doors. Black powder coated.
- Full length doors for maximum product capacity.
- Self closing doors. Positive seal, torsion type closure system.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.
- Entire cabinet structure is foamed-inplace using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

Bottom mounted units feature

- "No stoop" lower shelf to maximize product visibility.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning.

ROUGH-IN DATA

 $\label{eq:specifications} Specifications subject to change without notice. Chart dimensions rounded up to the nearest \equivalent matrix (millimeters rounded up to next whole number).$

			Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight (lbs.)	
Model	Doors	Shelves	W	D†	Н	HP	Voltage	Amps	Config.	• • •	(kg)
FLM-81F~TSL01	3	12	80¾	30¾	79	3⁄4	115/60/1	14.2	5-20P	9	870
			2051	772	2007	N/A		N/A		2.74	395

† Depth does not include 1%" (42 mm) for door handles.

INTRE USA	APPROVALS:	AVAILABLE AT:
10/21 Printed in U.S.A.		

Model:

FLM-81F~TSL01

Full Length Merchandiser: Swing Door Freezer with Hydrocarbon

Refrigerant~True Standard Look Version 01



STANDARD FEATURES

DESIGN

 True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in an attractive merchandiser that brilliantly displays packaged food and beverages.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains -10°F (-23.3°C) temperatures. Ideal for both frozen foods and ice cream.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Bottom mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to higher level.

CABINET CONSTRUCTION

PLAN VIEW

- Exterior non-peel or chip black powder coated cold rolled steel ends with black aluminum cabinet top and back; durable and permanent.
- Interior attractive, white aluminum liner with stainless steel floor.

- Insulation entire cabinet structure is foamedin-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with leg levelers.

DOORS

- Double pane thermal insulated glass swing doors with black powder coated frames.
- Door sign decal. Variety of decal options available.
- Each door fitted with 12" (305 mm) long extruded handle.
- Self closing doors. Positive seal, torsion type closure system.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Twelve (12) adjustable, solid white powder coated cantilever shelves, adjustable for up to 15° tilt in 5° increments. Three (3) white PVC coated wire floor racks.
- Shelves are 24½ "L X 21"D (623mm x 534 mm). Floor racks are 22½ "L X 20½"D (575mm x 591mm)

LIGHTING

NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE

WITHOUT NOTICE

• LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.

- Convenient clean-out drain built in cabinet floor.
- NSF/ANSI Standard 7 compliant for open food product.

ELECTRICAL

- Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 20 amp dedicated outlet.
- Unit utilizes a dual compressor system rated at 34 HP each.
- Cord and plug set included.



OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply.

- U White exterior.
- □ Stainless steel exterior.
- Black aluminum interior liner with black shelving.
- Clear aluminum interior liner.
- □ Stainless steel interior liner.
- All left hinge doors.
- All right hinge doors.
- U Wired cantilever shelves.
- Barrel locks located in grill assembly (requires one per door)
- Additional shelves.


Elevation Right

Plan

3D

Back

□ Product ID strips on shelves and floor racks.





TRUE MANUFACTURING CO	D., INC.
-----------------------	----------

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com

KCI

Model

FLM-81F~TSL01