

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

**Model: TBP60-54FDN** 

# Drop-in Type Bakery Display Cases

Refrigerated Bakery Cases

#### **Patented Self-Cleaning Condenser**



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.





\* Bottom portion will not be visible after installation

### = FEATURES & BENEFITS =

#### ■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

# Attractive, elegant, glass sided Euro design Straight tempered front & side glass with minimal frame provide full

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

#### ■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Sliding rear doors and front glass opening
  - Sliding rear doors make it easily accessible and convenient to arrange products. These doors are built to withstand constant sliding open and close. The front glass opens just enough to clean the interior effortlessly.
- Digital temperature controller
- Double pane glass is tempered for safety (Front heated glass)
- Adjustable, tempered glass shelves with AL front and back edges
- Stainless steel air flow grill and bottom glass shelf
- Rear access to compressor compartment for quick and easy service











Model	CU./FT.	# of Shelves	НР	AMPS	Watt (W)	Crated Weight (lbs.)	L x D x H* (inches)
TBP60-54FDN	21.8	2	3/4	8.7	1000.5	741	605/8 x 293/4 x 517/8

(unit: inch)

## **Model: TBP60-54FDN**

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	① NEMA 5-15P			
Full Load Amperes	8.7			
Watt (W)	1000.5			
Compressor HP	3/4			
Cord Length (ft.)	81/4			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	21.8			
Ext. Length Overall (in.)	60 <sub>5/8</sub> (1540mm)			
Ext. Depth Overall (in.)	293/4 (755mm)			
Ext. Height Overall (in.)*	517/8 (1318mm)			
Shelf Size (L x D) (in.)	56 x 15			
	56 x 13			
# of Shelves	2			
Net Weight (lbs.)	505			
Gross Weight (lbs.)	741			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

#### 2 Year Parts and Labor Warranty **WARRANTY: Additional 3 Year Warranty on Compressor**


#### STANDARD FEATURES

- · Front glass door lock standard
- · Self-contained system, no plumbing required
- · Safety shielded LED interior lighting
- 3" dia. swivel casters with locks on the rear set
- \*\* Lead time applies. Please contact your sales representative for more details to order.


#### ■ Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

### **PLAN VIEW**



**FRONT VIEW** 



NATURAL Refrigerant  ■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002







Ver.20200806





<sup>\*</sup> Height does not include 2-1/4" for caster height.