

Patented Self-Cleaning Condenser

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

	Qty:
SIS #:	
	SIS #:

Club Top Beer Dispensers

Model : TCB-2SDD-N6 TCB-2SBD-N6

Underbar Equipment

Super Deluxe Series



____ FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Forced air cooling system

Model

TCB-2SDD-N6

TCB-2SBD-N6

Fast cooling and balanced temperature throughout the cabinet.

Stainless steel cabinet construction

Super Deluxe (SDD) models boast a stainless steel exterior (except galvanized steel back and bottom). SBD models have an attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and club top lids are perfect for sanitation and durability. The interior is stainless steel except galvanized steel top. Spacious inside construction with 32" inner height accommodates various sizes of beer kegs. Turbo Air Club Top model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

Easy to glide stainless steel club top lids

3" diameter stainless steel insulated beer towers

Swing

Doors

2

2

1/2

Barrels

2

2

Digital Temperature Controller

External digital temperature control has an easily accessible panel to quickly adjust temperatures, which includes a defrost control.

- High-density polyurethane insulation The entire cabinet structure is foamed-in-place using high density, HCFC free polyurethane insulation.
- Comes standard with a four-way tapper manifold
- Club top (TCB) models provide easy access to the interior area

Club Top is a combined functional cabinet of direct draw cold beer dispenser and refrigerator. This convenient model provides easy access to interior storage area of the refrigerator for chilled bottles or cans.

- Ergonomically designed doors Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.
- Side mount compressor unit With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our innovative, front air intake feature also allows this model to be highly efficient in narrow spaces.
- Club top beer dispenser holds 33°F ~ 38°F for optimal beverage preservation

Refrigerant of Intertek				
	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)	
	1.3	357	587/8 x 271/4 x 385/8	
	1.3	357	587/8 x 271/4 x 385/8	

Ver.20220629 Printed in U.S.A Depth does not include 3/8" for door handles. Depth does not include 1-1/4" for rear spacers † Height does not include 3-1/8" for caster height. Height does not include 14-1/2" for draft arm.

HP

1/5

1/5

Club Top Beer Dispenser

(unit : inch)

271/4 (692mm)

Model : TCB-2SDD-N6, TCB-2SBD-N6

ELECTRICAL DATA				
Voltage		115/60/1		
Plug Type		(i) NEMA 5-15P		
Full Load Amperes		1.3		
Compressor HP		1/5		
Refrigerant		R-600a		
Cord Length (ft.)		8.5		
DIMENSION	AL DATA			
Net Capacity	1/2 Barrels	2		
	cu. ft.	20.9		
Ext. Length Ov	verall (in.)	587/8 (1495mm)		
Ext. Depth Overall (in.)*		271/4 (692mm)		
Ext. Height Overall (in.)†		385/8 (980mm)		
# of Swing Doors		2		
# of Casters		6EA		
Net Weight (lbs.)		335		
Gross Weight (lbs.)		357		

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 3/8" for door handles. Depth does not include 1-1/4" for rear spacers. † Height does not include 3-1/8" for caster height. Height does not include 14-1/2" for draft arm.

WARRANTY: 3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Double faucet beer tower
- Door locks
- Self-contained system
- 2.5" dia. swivel casters with locks on the front set

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake)
- 4" caster: G8F6500101(non-brake), G8F6500201 (w/brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" adjustable stainless steel leg: P0121P0100

lurbo air

• Triple faucet draft tower: 153A-3

Ver.20220629


ENERGY STAR®

Qualified




(GERMAN


KNIFE



PLAN VIEW

TOP VIEW





Turbo Air : 800-627-0032 **GK** : 800-500-3519

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

Texaking

manually . 000 501 +++0

Turbo air

