

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA #:	SIS #:	
CSI Section 11400		

Swing Door Freezers

____ FEATURES & BENEFITS ____

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures. · Alarms that sound when doors are not sealed shut; protect against food
- spoilage that originates from cold air leaks.
- · Early Warning Alarm program detects issues before malfunction occurs.
- · Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo Freeze)
- Smart defrost system will defrost as needed.
- · Automatic evaporator fan motor delays.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Energy conserving fan control

Utilizing algorithmic air circulation for optimal temperature levels, our innovative fan control system conserves energy by at least 15% and increases compressor life by up to 30%.

No electrical cabinet heater is needed

Turbo Air is the first in the industry to replace a frame heater with a method of using compressor-produced heat. This eliminates any unnecessary energy consumption while providing efficient freezing performance.

Shadow free advertising panel

Turbo Air is a pioneer in the refrigerator industry on applying special LED Light Guided Panels (LGP). LGP increases panel visibility and eliminates shadows, enhancing any store atmosphere with eye-catching effects. LED lighting offers 5 times longer lasting life than fluorescents and conserves energy as well.

High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, HCFC free polyurethane insulation.

Triple pane heated glass doors

Equipped with unique triple-pane heated glass doors which enhance energy efficiency by preventing heat transfers and minimizing condensation. Lightweight door construction reduces door maintenance, bushing wear, and facilitates smooth door opening.

LED interior lighting



Model : TGF-47SD*-N



TGF-47SDW-N

Patented Self-Cleaning Condenser



■ Freezer holds -10°F ~ 5°F for the best in frozen food preservation

Only at Turbo Air, Only in the World Turbo Air's 2 &3 Glass Door Freezers are powered by 115V. Not only is our 115V simple and easy to plug in and operate, it also saves customers over \$1,000 in electrical line installation for 220V powered glass door freezers. We are the only company to have achieved this feat, which is proof of our dedication to energy efficiency and the environment.

NATURAL Refrigerant		US STEAR THE STARE		
AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)		

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)
TGF-47SD*-N	2	39	8	3/4	10.4	590	511/8 x 317/8 x 77

Ver 20210719 Printed in U.S.A.

* Depth does not include 2-1/4" (57mm) for door handle. † Height does not include 2-1/2" (63mm) for leg height. *White cabinet(W), Black cabinet(B).

Swing Door Freezers

Model : TGF-47SD*-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	• NEMA 5-20P			
Full Load Amperes / LRA	10.4 / 49			
Compressor HP	3/4			
Cord Length (ft.)	7			
Refrigerant	R-290			
DIMENSIONAL DATA				
# of Doors	2			
Net Capacity (cu. ft.)	39			
Ext. Length Overall (in.)	511/8 (1299mm)			
Ext. Depth Overall (in.)*	317/8 (809mm)			
Ext. Height Overall (in.) [†]	77 (1956mm)			
Int. Length Overall (in.)	471/4 (1199mm)			
Int. Depth Overall (in.)	271/2 (699mm)			
Int. Height Overall (in.)	603/8 (1535mm)			
# of Shelves	8			
Shelf Size (L x D) (in.)	221/2 x 23			
Net Weight (lbs.)	513			
Gross Weight (lbs.)	590			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2-1/4" (57mm) for door handle. † Height does not include 2-1/2" (63mm) for leg height.

3 Year Parts and Labor Warranty WARRANTY : Additional 4 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Door locks standard
- * Two color options available (standard): Super Deluxe series comes in white cabinet (W), black cabinet with black color trim (B).

OPTIONAL ACCESSORIES

- 4" caster, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- Additional PE coated wire shelf: P0178Q0100(Left), P0178F0110(Right)
- Price tag channel: P0122K5400 (21-1/2"L)
- Sign panel (blank): P0145A1020

SPEC


lurbo air


NATURAL


Refrigerant



(unit : inch)








Ver.20210719





Turbo air

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

Texaking

(GEAMAN) |KNIFE) Continued product development may necessitate specification changes without notice.

ENERGY STAR®

Qualified