

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Mega-Top Prep Table+Work Station

Food Prep Tables Super Deluxe Series

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

Model : TST-72SD-15M-N(-LW)



\equiv FEATURES & BENEFITS \equiv

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior (ABS door liner) and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving

- Insulated pan cover
- Clear lid available (TST-72SD-15M-N-CL)
- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail

- Refrigerator holds 33°F ~ 39°F for the best in food preservation
- TST-72SD-15M-N: Right side work station
- TST-72SD-15M-N-LW: Left side work station

1	cool inner temperature.	1			I		frigerant		S. A
	Model	Swing Doors	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)
	TST-72SD-15M-N(-LW)	3	23	3	15	3/8	9.9	392	725/8 x 34 x 39

Ver 20210706 Printed in U.S.A.

* Depth does not include 3" for cutting board and 1" for rear spacers. † Height does not include 5" for caster height.

Mega-Top Prep Table+Work Station

(unit : inch)

Model : TST-72SD-15M-N(-LW)

ELECTRICAL DATA					
Voltage	115/60/1 (i) NEMA 5-15				
Plug Type					
Full Load Amperes	9.9				
Compressor HP	3/8				
Cord Length (ft.)	10				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	725/8 (1846mm)				
Ext. Depth Overall (in.)*	34 (864mm)				
Ext. Height Overall (in.)†	39 (992mm)				
# of Doors	3				
# of Shelves	3				
# of Pans	15				
# of Hood	1				
Net Capacity (cu. ft.)	23				
Shelf Size (L x D) (in.)	21 x 17 (Left/Right)				
	23 x 17 (Middle)				
Net Weight (lbs.)	352				
Gross Weight (lbs.)	392				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 3" for cutting board and 1" for rear spacers.

+ Height does not include 5" for caster height.

WARRANTY : 3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: M727800100 (Left/Right), M727800300 (Middle)
- Removable food cover: RCT-36-15
- Single overshelf, stainless steel, 72-13/16" W: TSOS-6S
- Double overshelf, 18/304 stainless steel, 72-1/2" W: TSOS-6R

U. S.

· Door lock: lead time applies. Please contact your sales representative for more details to order.


> ((Tb) (II) 7 YEAR WARRANTY YEAI

> > (GERMAN

KNIFE


Ver.20210706

Continued product development may necessitate specification changes without notice.



PLAN VIEW

TOP VIEW





Turbo Air : 800-627-0032 **GK** : 800-500-3519 ■ Warranty : 800-381-7770 ■ AC : 888-900-1002

Turbo air

Texaking



Intertek

NATURAL

Refrigerant